

Specifications

Input	VGA x 1, HDMI x 1 , HD/SD-SDI x 1, Analog Audio L/R
Output	SDI x 2, HDMI x 1, SDI Loop thru BNC(front panel)
Mini USB	<ul style="list-style-type: none"> • Firmware upgrade • Aspect Mode selection
Supported Video Input Format	<ul style="list-style-type: none"> • SDI (YUV) input 3G-SDI: 1080p60/50 1080p59.94 HD-SDI: 1080i60/50, 1080p30/25/24, 720p60/50 1080i59.94, 1080p29.97, 1080p23.98, 720p59.94 • SD-SDI(YUV): 525i, 625i • HDMI(YUV/RGB): 1080p60/50, 1080i60/50, 1080p30/25/24, 720p60/50 1080p59.94, 1080i59.94, 720p59.94, 1080p29.97 1080p23.98, 480p, 576p 800x600@60Hz, 1024x768@60Hz, 1280x1024@60Hz 1366x768@60Hz, 1400x1050@60Hz, 1600x1200@60Hz • VGA: 800x600@60Hz, 1024x768@60Hz, 1280x1024@60Hz 1366x768@60Hz, 1400x1050@60Hz, 1600x1200@60Hz • HDMI Supports YUV / RGB color space
Supported Video Output Format	<p>SDI / HDMI 1080p60/50, 1080p59.94, 1080p23.98/29.97/24/25/30 1080i60/50 ; 720P60/50 1080i59.94 ; 720P59.94, 525i, 625i</p> <ul style="list-style-type: none"> • SDI/HDMI output supports YUV 4:2:2
Supported Audio Format	<ul style="list-style-type: none"> • Input Analog Audio L/R : stereo audio SDI / HDMI embedded audio up to 8CH, 48KHz, PCM audio HDMI embedded audio: up to 8CH, 44.1/48/96KHz, PCM audio • Output SDI embedded audio up to 8CH, 48KHz, PCM audio HDMI embedded audio: up to 8CH, 48KHz, PCM audio
Power Consumption	12V/1A (7.2W)
Operating Temperature	0~50°C [32~114°F]
Storage Temperature	-10~ +60°C
Dimension	144.8mm(L) x 85mm(W) x 45.2mm(H)
Certifications	CE / FCC