

X8 specifications

Description	X8 passive 2-way coaxial enclosure, amplified by LA4X / LA8.
Usable bandwidth (-10 dB)	60 Hz - 20 kHz
Maximum SPL ¹	127 dB ([X8])
Nominal directivity	Vertical: Axisymmetric 100°
Monitoring angle	35°
Transducers	1 × 8" weather-resistant, bass-reflex laminar vents. 1 × 1.5" compression driver, neodymium, weather-resistant, partial horn.
Nominal impedance	LF: 8 Ω HF: 8 Ω
Connectors	IN: SpeakON LINK: SpeakON
Rigging and handling	1 × handles DIN580-compatible M8 threaded insert 4 × M10 threaded inserts 1 × 35 mm pole sockets
Weight (net)	12 kg / 26.5 lb
Cabinet	First grade Baltic beech and birch plywood
Finish	Dark Grey brown PANTONE 426C Pure white RAL 9010 Custom RAL code on special order
IP	IP43

¹ Peak level at 1 m under free field conditions using 10 dB crest factor pink noise with specified preset.

X8 dimensions

On-end H/W/D

424 mm / 250 mm / 264 mm
16.7 in / 9.8 in / 10.4 in

Monitor H/W/D

278 mm / 424 mm / 306 mm
10.9 in / 16.7 in / 12 in

